

Silver-Line Plastics

PVC SDR 26 PR 160 PVC 1120 TYPE I GRADE 1

Nominal Size	Item Number	Bar Code 717141	Outside Diameter	Min. Wall Thickness	Wt/100'	Ft/Pallet	Max Working Pressure at 73° F
1-1/4"	32.122	32122 1	1.660	0.064	21	5,000	160 PSI
1-1/2"	32.152	32152 8	1.900	0.073	28	4,500	160 PSI
2"	32.202	32202 0	2.375	0.091	43	2,800	160 PSI
2-1/2"	32.252	32252 5	2.875	0.110	62	1,160	160 PSI
3"	32.302	32302 7	3.500	0.135	93	1,500	160 PSI
4"	32.402	32402 4	4.500	0.173	156	1,140	160 PSI
5"	32.502	32502 1	5.563	0.214	240	460	160 PSI
6"	32.602	32602 8	6.625	0.255	320	520	160 PSI

Note: 2" – 6" are Laying Length

NSF- pw

PVC SDR 26 conforms to ASTM D 2241; 4" - 6" also meets ASTM F 480

Material complies with ANSI / NSF Standard 61

TOO MUCH CEMENT WILL DAMAGE THE PIPE
PVC PIPE NOT RECOMMENDED FOR AIR PRESSURE