

## *Silver-Line Plastics*

**PVC WELL CASING PVC 1120 TYPE I GRADE1**

**BELLED END 20 FT. LENGTHS**

Nomina Siz	Item	Bar 7	Outsid Diamete	Min. Thicknes	Wt/100	Bell (inch	Ft/	SD
4-	34.44	34442	4.95	0.291	275	6 1/4	520	17
4-1/2"	34.452	34452 7	4.950	0.236	229	6 1/4	520	21
4-1/2"	32.452	32452 9	4.950	0.190	187	6 1/4	520	26
5"	34.512	34512 8	5.563	0.327	360	7 1/4	460	17
6"	34.642	34642 2	6.625	0.390	496	7 1/4	520	17
6-1/4"	34.742	34742 9	6.900	0.406	545	7 1/4	660	17
6-1/8" I.D.	34.612	34612 5	6.900	0.329	445	7 1/4	660	21
6-1/4" I.D.	34.622	34622 4	6.900	0.250	345	7 1/4	660	27.6

Note: All Sizes Are Laying Length and IC-2 Rated

NSF-wc

**PVC SCH 40 WELL CASING PVC 1120 TYPE I GRADE1 BELLED END 20 FT. LENGTHS**

Nominal Size	Item Number	Bar Code 7 17141	Outside Diameter	Min. Wall Thickness	Wt/100'	Bell Depth (inch)	Ft/Pallet
2"	35.202	35202 7	2.375	0.154	70	3 1/2	2,800
3"	35.302	35302 4	3.500	0.216	144	5 1/4	1,500
4"	35.402	35402 1	4.500	0.237	205	6	1,140
5"	35.502	35502 8	5.563	0.258	288	7	460
6"	35.602	35602 5	6.625	0.280	364	7 1/4	520
8"	35.802	35802 9	8.625	0.322	546	7 1/4	280
10"	35.910	35910 1	10.750	0.365	753	8	220
12"	35.912	35912 5	12.750	0.406	1000	9 1/2	80

Note: 2" – 8" Are Laying Length and 4"–8" Are IC-2 Rated

NSF-wc & NSF-pw

**PVC SDR 21 WELL CASING PVC 1120 TYPE I GRADE1 BELLED END 20 FT. LENGTHS**

Nominal Size	Item Number	Bar Code 7 17141	Outside Diameter	Min. Wall Thickness	Wt/100'	Bell Depth (inch)	Ft/Pallet
2"	34.202	34202 8	2.375	0.113	53	3 1/2	2,800
3"	34.302	34302 5	3.500	0.167	114	5 1/4	1,500
4"	34.402	34402 2	4.500	0.214	189	6	580
5"	34.502	34502 9	5.563	0.265	295	7	460
6"	34.602	34602 6	6.625	0.316	390	7 1/4	520

Note: 2" – 6" Are Laying Length and 5" and 6" Are IC-2 Rated

NSF-wc & NSF-pw

**PVC SDR 26 WELL CASING PVC 1120 TYPE I GRADE1 BELLED END 20 FT. LENGTHS**

Nominal Size	Item Number	Bar Code 7 17141	Outside Diameter	Minimum Wall Thickness	Wt/100'	Bell Depth (inch)	Ft/Pallet
4"	32.402	32402 4	4.500	0.173	156	6	1,140
5"	32.502	32502 1	5.563	0.214	240	7	460
6"	32.602	32602 8	6.625	0.255	320	7 1/4	520

Note: 4" – 6" Are Laying Length and 5" Is IC-2 Rated

NSF-wc & NSF-pw

Material complies with ANSI / NSF Standard 61 and ASTM F 480