

*Silver-Line Plastics***Sil-O-Flex Ultra Turf Polyethylene Pipe**

IPS (Iron Pipe Size) 100 PSI PE 3408 SIDR 15

Nominal Size	Item Number	Bar Code	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
1"	20.103	20103 5	300'	1.049	1.189	0.070	100 PSI	11

NSF-PW

IPS (Iron Pipe Size) 80 PSI PE 3408 SIDR 19

Nominal Size	Item Number	Bar Code	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
1"	19.103	19103 9	300'	1.049	1.179	0.065	80 PSI	10

Sil-O-Flex (SIDR-PR) Polyethylene pipe is NSF listed and conforms to ASTM D 2239

NSF-PW

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

**Max-Flo Utility Grade Polyethylene Pipe\***

100 PSI SIDR 15 UTILITY GRADE PE (not NSF listed)

Nominal Size	Item Number	Bar Code	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
1/2"	18.051	18051 4	100'	0.622	0.742	0.060	100 PSI	6
	18.054	18054 5	400'					
3/4"	18.071	18071 2	100'	0.824	0.944	0.060	100 PSI	7
	18.074	18074 3	400'					
1"	18.101	18101 6	100'	1.049	1.189	0.070	100 PSI	11
	18.103	18103 0	300'					
1-1/4"	18.121	18121 4	100'	1.380	1.564	0.092	100 PSI	19
	18.123	18123 8	300'					
1-1/2"	18.151	18151 1	100'	1.610	1.824	0.107	100 PSI	25
	18.157	18157 3	250'					
2"	18.201	18201 3	100'	2.067	2.343	0.138	100 PSI	43
	18.202	18202 0	200'					

80 PSI SIDR 19 UTILITY GRADE PE (not NSF listed)

Nominal Size	Item Number	Bar Code	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	30.071	30071 4	100'	0.824	0.944	0.060	80 PSI	7
	30.074	30074 5	400'					
1"	30.101	30101 8	100'	1.049	1.169	0.060	80 PSI	10
	30.103	30103 2	300'					
1-1/4"	30.121	30121 6	100'	1.380	1.526	0.073	80 PSI	15
1-1/2"	30.151	30151 3	100'	1.610	1.780	0.085	80 PSI	20
2"	30.201	30201 5	100'	2.067	2.285	0.109	80 PSI	33

IPS - SIDR UTILITY GRADE PE (not NSF listed)

Nominal Size	Item Number	Bar Code	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F
1-1/2"	20.151	20151 6	100'	1.610	1.780	General Purpose	60 PSI
	20.157	20157 8	250'				
2"	22.205	22205 4	50'	2.067	2.285	General Purpose	50 PSI
	22.201	22201 6	100'				
	22.202	22202 3	200'				

\*Manufactured from Polyethylene - Not NSF listed

Standard Silver-Line Warranty Applies