

Silver-Line Plastics

Sil-O-Flex HDPE Water Service Pipe & Tubing 50 Year Warranty

CTS(Copper Tube Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR9 (Tracer Tube®)

Nominal Size	Our Item Number	Bar Code 7 1 71 41	Coil Length	(Value) Inside Diameter	Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73°F	Wt/100'
3/4"	23.071	23 07 14	10 0'	0.681	0.875	0.097	200 PSI	10
	23.075	23 07 52	50 0'					
1"	23.101	23 10 18	10 0'	0.875	1.125	0.125	200 PSI	17
	23.103	23 10 32	30 0'					
1-1/4"	23.121	23 12 16	10 0'	1.069	1.375	0.153	200 PSI	26
	23.123	23 12 30	30 0'					
1-1/2"	23.151	23 15 13	10 0'	1.263	1.625	0.181	200 PSI	36
	23.153	23 15 37	30 0'					
2"	23.201	23 20 15	10 0'	1.653	2.125	0.236	200 PSI	61
	23.202	23 20 22	20 0'					

Sil-O-Flex (CTS) Polyethylene pipe is NSF listed and conforms to ASTM D 2737

NSF-PW

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

Available in Sil-O-Flex Blue Stripe (extruded blue stripes in wall of pipe)

Tracer Tube® - a combined package of a 12 AWG, UL listed solid copper conductor wire securely attached to the tubing.

IPS (Iron Pipe Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR7

Nominal Size	Our Item Number	Bar Code 7 1 71 41	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73°F	Wt/100'
3/4"	25.071	25 07 12	10 0'	0.824	1.060	0.118	200 PSI	15
	25.074	25 07 43	40 0'					
1"	25.101	25 10 16	10 0'	1.049	1.349	0.150	200 PSI	25
	25.103	25 10 30	30 0'					
1-1/4"	25.121	25 12 14	10 0'	1.380	1.774	0.197	200 PSI	43
	25.123	25 12 38	30 0'					
1-1/2"	25.151	25 15 11	10 0'	1.610	2.070	0.230	200 PSI	59
	25.157	25 15 73	25 0'					
2"	25.201	25 20 13	10 0'	2.067	2.657	0.295	200 PSI	96
	25.202	25 20 20	20 0'					

Sil-O-Flex (SDR-P R) Polyethylene pipe is NSF listed and conforms to ASTM D 2239

NSF-PW

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

Available in Sil-O-Flex Blue Stripe (extruded blue stripes in wall of pipe)

IPS (Iron Pipe Size) 160 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR9

Nominal Size	Our Item Number	Bar Code 7 1 71 41	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73°F	Wt/100'
3/4"	26.071	26 07 11	10 0'	0.824	1.008	0.092	160 PSI	12
	26.074	26 07 42	40 0'					
1"	26.101	26 10 15	10 0'	1.049	1.283	0.117	160 PSI	19
	26.102	26 10 22	20 0'					
	26.103	26 10 39	30 0'					
	26.115	26 11 52	50 0'					
1-1/4"	26.121	26 12 13	10 0'	1.380	1.686	0.153	160 PSI	33
	26.123	26 12 37	30 0'					
1-1/2"	26.151	26 15 10	10 0'	1.610	1.968	0.179	160 PSI	44
	26.157	26 15 72	25 0'					
2"	26.201	26 20 12	10 0'	2.067	2.527	0.230	160 PSI	73
	26.202	26 20 29	20 0'					

Sil-O-Flex (SDR-P R) Polyethylene pipe is NSF listed and conforms to ASTM D 2239

NSF-PW

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

Available in Sil-O-Flex Blue Stripe (extruded blue stripes in wall of pipe)

Silver-Line Plastics

IPS (Iron Pipe Size) 100 PSI PE 3608 or PE 3710 (formerly PE 3408) SI DR 15

Nominal Size	Our Item Number	Bar Code 7 1 7 141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73 °F	Wt/1 00'
3/4"	27.071	270710	10 0'	0.824	0.944	0.060	100 PSI	7
	27.074	270741	40 0'					
1"	27.101	271014	10 0'	1.049	1.189	0.070	100 PSI	11
	27.103	271038	30 0'					
1-1/4"	27.121	271212	10 0'	1.380	1.564	0.092	100 PSI	19
	27.123	271236	30 0'					
1-1/2"	27.151	271519	10 0'	1.610	1.824	0.107	100 PSI	25
	27.157	271571	25 0'					
2"	27.201	272011	10 0'	2.067	2.343	0.138	100 PSI	42
	27.202	272028	20 0'					

Sil-O-Flex (SIDR -PR) Polyethylene pipe is NSF listed and conforms to **ASTMD 2239**

N SF-PW

Material complies with ANSI / NSFS standard 61 and meets the requirements of AWWAC 901 on the 2"

O.D. Controlled 160 PSI PE 3608 or PE 3710 (formerly PE 3408) DR 11

Nominal Size	Our Item Number	BarCode 7 17141	Coil Length	Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73°F	Wt/1 00'
* 3/4"	08.071	080715	10 0'	1.050	0.095	160 PSI	12
	08.075	080743	50 0'				
* 1"	08.101	081019	10 0'	1.315	0.120	160 PSI	20
	08.105	081057	50 0'				
1-1/4"	08.121	081217	10 0'	1.660	0.151	160 PSI	31
	08.125	081255	50 0'				
1-1/2"	08.151	081514	10 0'	1.900	0.173	160 PSI	41
	08.155	081552	30 0'				
2"	08.201	082016	10 0'	2.375	0.216	160 PSI	64
	08.202	082023	20 0'				

Sil-O-Flex (DR-PR) Polyethylene pipe is NSF listed and conforms to **ASTMD 3035**

N SF-PW

Material complies with ANSI / NSFS standard 61 and meets the requirements of AWWAC 901

* Sizes 3/4" and 1" Also available in Silver-Line Ultra Pure // Solid Blue PE 3608