

Silver-Line Plastics

Ultra-Pure® HDPE Water Service Pipe & Tubing (Blue) Lifetime Warranty

CTS (Copper Tube Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR9 Tracer Tube®

Nominal Size	Our Item Number	Bar Code 7 1 71 41	Coil Length	(Value) Inside Diameter	Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73°F	Wt/1 0 0'
3/4"	1 1 .0 71	11 07 19	10 0'	0 .6 81	0.8 75	0 .0 97	20 0 PSI	10
	1 1 .0 75	11 07 57	50 0'					
1"	1 1 .1 01	11 10 13	10 0'	0 .8 75	1.1 25	0.1 25	20 0 PSI	17
	1 1 .1 03	11 10 37	30 0'					
1-1 /4"	1 1 .1 21	11 12 11	10 0'	1 .0 69	1 .3 75	0.1 53	20 0 PSI	26
	1 1 .1 23	11 12 35	30 0'					
1-1 /2"	1 1 .1 51	11 15 18	10 0'	1 .2 63	1 .6 25	0.1 81	2 00 P SI	36
	1 1 .1 53	11 15 32	30 0'					
2"	1 1 .2 01	11 20 10	10 0'	1 .6 53	2 .1 25	0.2 36	2 00 P SI	61
	1 1 .2 02	11 20 27	20 0'					

Ultra-Pure® (CTS) Polyethylene pipe is NSF listed and conforms to ASTM D 2737 N SF-PW

Material complies with ANSI / NSF Standard 61, and meets the requirements of AWWAC 901

Also available in Silver-Line Ultra Pure II Solid Blue PE 3608

Tracer Tube® - a combined package of a 12 AWG, UL listed solid copper conductor wire securely attached to the tubing.

IPS (Iron Pipe Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR7

Nominal Size	Our Item Number	Bar Code 7 1 71 41	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73 °F	Wt/1 00'
3 /4"	1 4 .0 71	14 07 16	10 0'	0.8 24	1 .0 60	0.1 18	2 00 P SI	15
	1 4 .0 74	14 07 47	40 0'					
1"	1 4 .1 01	14 10 10	10 0'	1.0 49	1.3 49	0 .1 50	20 0 PSI	25
	1 4 .1 03	14 10 34	30 0'					
1-1 /4"	1 4 .1 21	14 12 18	10 0'	1.3 80	1 .7 74	0.1 97	20 0 PSI	43
	1 4 .1 23	14 12 32	30 0'					
1 -1 /2"	1 4 .1 51	14 15 15	10 0'	1 .6 10	2.0 70	0.2 30	2 00 P SI	59
	1 4 .1 57	14 15 77	25 0'					
2"	1 4 .2 01	14 20 17	10 0'	2.0 67	2.6 57	0.2 95	20 0 PSI	96
	1 4 .2 02	14 20 24	20 0'					

Ultra-Pure® (SIDR-PR) Polyethylene pipe is NSF listed and conforms to AS TM D 2239 N S F-PW

Material complies with ANSI / NSF Standard 61, and meets the requirements of AWWAC 901

Also available in Silver-Line Ultra Pure II Solid Blue PE 3608

IPS (Iron Pipe Size) 160 PSI PE 3608 or PE 3710 (formerly PE 3408) SI DR9

Nominal Size	Our Item Number	Bar Code 7 1 71 41	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73 °F	Wt/1 00'
3/4"	0 6 .0 71	06 07 17	10 0'	0.8 24	1.0 08	0.0 92	16 0 PSI	12
	0 6 .0 74	06 07 48	40 0'					
1"	0 6 .1 01	06 10 11	10 0'	1.0 49	1 .2 83	0.1 17	16 0 PSI	19
	0 6 .1 03	06 10 35	30 0'					
1 -1 /4"	0 6 .1 21	06 12 19	10 0'	1 .3 80	1.6 86	0.1 53	1 60 P SI	33
	0 6 .1 23	06 12 33	30 0'					
1 -1 /2"	0 6 .1 51	06 15 16	10 0'	1 .6 10	1.9 68	0 .1 79	16 0 PSI	44
	0 6 .1 57	06 15 78	25 0'					
2"	0 6 .2 01	06 20 18	10 0'	2.0 67	2.5 27	0.2 30	16 0 PSI	73
	0 6 .2 02	06 20 25	20 0'					

Ultra-Pure® (SIDR-PR) Polyethylene pipe is NSF listed and conforms to AS TM D 2239 N S F-PW

Material complies with ANSI/NSF Standard 61, and meets the requirements of AWWAC 901

Also available in Silver-Line Ultra Pure II Solid Blue PE 3608