

## Sil-O-Flex Ultra Turf Polyethylene Pipe

IPS (Iron Pipe Size) 100 PSI PE 3408 SIDR 15

Nominal Size	Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
1"	20.103	20103 5	300'	1.049	1.189	0.070	100 PSI	11

NSF-PW

IPS (Iron Pipe Size) 80 PSI PE 3408 SIDR 19

Nominal Size	Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
1"	19.103	19103 9	300'	1.049	1.179	0.065	80 PSI	10

Sil-O-Flex (SIDR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 2239**

NSF-PW

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

## Max-Flo Utility Grade Polyethylene Pipe\*

100 PSI SIDR 15 UTILITY GRADE PE (not NSF listed)

Nominal Size	Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
1/2"	18.051	18051 4	100'	0.622	0.742	0.060	100 PSI	6
	18.054	18054 5	400'					
3/4"	18.071	18071 2	100'	0.824	0.944	0.060	100 PSI	7
	18.074	18074 3	400'					
1"	18.101	18101 6	100'	1.049	1.189	0.070	100 PSI	11
	18.103	18103 0	300'					
1-1/4"	18.121	18121 4	100'	1.380	1.564	0.092	100 PSI	19
	18.123	18123 8	300'					
1-1/2"	18.151	18151 1	100'	1.610	1.824	0.107	100 PSI	25
	18.157	18157 3	250'					
2"	18.201	18201 3	100'	2.067	2.343	0.138	100 PSI	43
	18.202	18202 0	200'					

80 PSI SIDR 19 UTILITY GRADE PE (not NSF listed)

Nominal Size	Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	30.071	30071 4	100'	0.824	0.944	0.060	80 PSI	7
	30.074	30074 5	400'					
1"	30.101	30101 8	100'	1.049	1.169	0.060	80 PSI	10
	30.103	30103 2	300'					
1-1/4"	30.121	30121 6	100'	1.380	1.526	0.073	80 PSI	15
1-1/2"	30.151	30151 3	100'	1.610	1.780	0.085	80 PSI	20
2"	30.201	30201 5	100'	2.067	2.285	0.109	80 PSI	33

IPS - SIDR UTILITY GRADE PE (not NSF listed)

Nominal Size	Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F
1-1/2"	20.151	20151 6	100'	1.610	1.780	General Purpose	60 PSI
	20.157	20157 8	250'				
2"	22.205	22205 4	50'	2.067	2.285	General Purpose	50 PSI
	22.201	22201 6	100'				
	22.202	22202 3	200'				

\*Manufactured from Polyethylene - Not NSF listed

Standard Silver-Line Warranty Applies