

## Sil-O-Flex HDPE Water Service Pipe & Tubing 50 Year Warranty

### CTS(Copper Tube Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR 9 (Tracer Tube®)

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	(Value) Inside Diameter	Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	23.071	23071 4	100'	0.681	0.875	0.097	200 PSI	10
	23.075	23075 2	500'					
1"	23.101	23101 8	100'	0.875	1.125	0.125	200 PSI	17
	23.103	23103 2	300'					
1-1/4"	23.121	23121 6	100'	1.069	1.375	0.153	200 PSI	26
	23.123	23123 0	300'					
1-1/2"	23.151	23151 3	100'	1.263	1.625	0.181	200 PSI	36
	23.153	23153 7	300'					
2"	23.201	23201 5	100'	1.653	2.125	0.236	200 PSI	61
	23.202	23202 2	200'					

Sil-O-Flex (CTS) Polyethylene pipe is NSF listed and conforms to **ASTM D 2737**

**NSF-PW**

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

Available in Sil-O-Flex Blue Stripe (extruded blue stripes in wall of pipe)

**Tracer Tube®** - a combined package of a 12 AWG, UL listed solid copper conductor wire securely attached to the tubing.

### IPS (Iron Pipe Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SIDR 7

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	25.071	25071 2	100'	0.824	1.060	0.118	200 PSI	15
	25.074	25074 3	400'					
1"	25.101	25101 6	100'	1.049	1.349	0.150	200 PSI	25
	25.103	25103 0	300'					
1-1/4"	25.121	25121 4	100'	1.380	1.774	0.197	200 PSI	43
	25.123	25123 8	300'					
1-1/2"	25.151	25151 1	100'	1.610	2.070	0.230	200 PSI	59
	25.157	25157 3	250'					
2"	25.201	25201 3	100'	2.067	2.657	0.295	200 PSI	96
	25.202	25202 0	200'					

Sil-O-Flex (SIDR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 2239**

**NSF-PW**

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

Available in Sil-O-Flex Blue Stripe (extruded blue stripes in wall of pipe)

### IPS (Iron Pipe Size) 160 PSI PE 3608 or PE 3710 (formerly PE 3408) SIDR 9

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	26.071	26071 1	100'	0.824	1.008	0.092	160 PSI	12
	26.074	26074 2	400'					
1"	26.101	26101 5	100'	1.049	1.283	0.117	160 PSI	19
	26.102	26102 2	200'					
	26.103	26103 9	300'					
	26.115	26115 2	500'					
1-1/4"	26.121	26121 3	100'	1.380	1.686	0.153	160 PSI	33
	26.123	26123 7	300'					
1-1/2"	26.151	26151 0	100'	1.610	1.968	0.179	160 PSI	44
	26.157	26157 2	250'					
2"	26.201	26201 2	100'	2.067	2.527	0.230	160 PSI	73
	26.202	26202 9	200'					

Sil-O-Flex (SIDR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 2239**

**NSF-PW**

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

Available in Sil-O-Flex Blue Stripe (extruded blue stripes in wall of pipe)

**IPS (Iron Pipe Size) 100 PSI PE 3608 or PE 3710 (formerly PE 3408) SIDR 15**

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	27.071	27071 0	100'	0.824	0.944	0.060	100 PSI	7
	27.074	27074 1	400'					
1"	27.101	27101 4	100'	1.049	1.189	0.070	100 PSI	11
	27.103	27103 8	300'					
1-1/4"	27.121	27121 2	100'	1.380	1.564	0.092	100 PSI	19
	27.123	27123 6	300'					
1-1/2"	27.151	27151 9	100'	1.610	1.824	0.107	100 PSI	25
	27.157	27157 1	250'					
2"	27.201	27201 1	100'	2.067	2.343	0.138	100 PSI	42
	27.202	27202 8	200'					

Sil-O-Flex (SIDR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 2239**

**NSF-PW**

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901 on the 2"

**O.D. Controlled 160 PSI PE 3608 or PE 3710 (formerly PE 3408) DR 11**

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
* 3/4"	08.071	08071 5	100'	1.050	0.095	160 PSI	12
	08.075	08074 3	500'				
* 1"	08.101	08101 9	100'	1.315	0.120	160 PSI	20
	08.105	08105 7	500'				
1-1/4"	08.121	08121 7	100'	1.660	0.151	160 PSI	31
	08.125	08125 5	500'				
1-1/2"	08.151	08151 4	100'	1.900	0.173	160 PSI	41
	08.155	08155 2	300'				
2"	08.201	08201 6	100'	2.375	0.216	160 PSI	64
	08.202	08202 3	200'				

Sil-O-Flex (DR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 3035**

**NSF-PW**

Material complies with ANSI / NSF Standard 61 and meets the requirements of AWWA C 901

\* Sizes 3/4" and 1" Also available in Silver-Line Ultra Pure // Solid Blue PE 3608