

Ultra-Pure® HDPE Water Service Pipe & Tubing (Blue) Lifetime Warranty

CTS (Copper Tube Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SDR 9

Tracer Tube®

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	(Value) Inside Diameter	Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	11.071	11071 9	100'	0.681	0.875	0.097	200 PSI	10
	11.075	11075 7	500'					
1"	11.101	11101 3	100'	0.875	1.125	0.125	200 PSI	17
	11.103	11103 7	300'					
1-1/4"	11.121	11121 1	100'	1.069	1.375	0.153	200 PSI	26
	11.123	11123 5	300'					
1-1/2"	11.151	11151 8	100'	1.263	1.625	0.181	200 PSI	36
	11.153	11153 2	300'					
2"	11.201	11201 0	100'	1.653	2.125	0.236	200 PSI	61
	11.202	11202 7	200'					

Ultra-Pure® (CTS) Polyethylene pipe is NSF listed and conforms to **ASTM D 2737**

NSF-PW

Material complies with ANSI / NSF Standard 61, and meets the requirements of AWWA C 901

Also available in Silver-Line Ultra Pure // Solid Blue PE 3608

Tracer Tube® - a combined package of a 12 AWG, UL listed solid copper conductor wire securely attached to the tubing.

IPS (Iron Pipe Size) 200 PSI PE 3608 or PE 3710 (formerly PE 3408) SIDR 7

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	14.071	14071 6	100'	0.824	1.060	0.118	200 PSI	15
	14.074	14074 7	400'					
1"	14.101	14101 0	100'	1.049	1.349	0.150	200 PSI	25
	14.103	14103 4	300'					
1-1/4"	14.121	14121 8	100'	1.380	1.774	0.197	200 PSI	43
	14.123	14123 2	300'					
1-1/2"	14.151	14151 5	100'	1.610	2.070	0.230	200 PSI	59
	14.157	14157 7	250'					
2"	14.201	14201 7	100'	2.067	2.657	0.295	200 PSI	96
	14.202	14202 4	200'					

Ultra-Pure® (SIDR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 2239**

NSF-PW

Material complies with ANSI / NSF Standard 61, and meets the requirements of AWWA C 901

Also available in Silver-Line Ultra Pure // Solid Blue PE 3608

IPS (Iron Pipe Size) 160 PSI PE 3608 or PE 3710 (formerly PE 3408) SIDR 9

Nominal Size	Our Item Number	Bar Code 7 17141	Coil Length	Inside Diameter	(Value) Outside Diameter	Min. Wall Thickness	Max Working Pressure at 73° F	Wt/100'
3/4"	06.071	06071 7	100'	0.824	1.008	0.092	160 PSI	12
	06.074	06074 8	400'					
1"	06.101	06101 1	100'	1.049	1.283	0.117	160 PSI	19
	06.103	06103 5	300'					
1-1/4"	06.121	06121 9	100'	1.380	1.686	0.153	160 PSI	33
	06.123	06123 3	300'					
1-1/2"	06.151	06151 6	100'	1.610	1.968	0.179	160 PSI	44
	06.157	06157 8	250'					
2"	06.201	06201 8	100'	2.067	2.527	0.230	160 PSI	73
	06.202	06202 5	200'					

Ultra-Pure® (SIDR-PR) Polyethylene pipe is NSF listed and conforms to **ASTM D 2239**

NSF-PW

Material complies with ANSI / NSF Standard 61, and meets the requirements of AWWA C 901

Also available in Silver-Line Ultra Pure // Solid Blue PE 3608