

Silver-Line Plastics

PVC DWV SCHEDULE 40 COEX CELLULAR CORE

PLAIN END

Nominal Size	Item Number		Bar Code 7 14141		Outside Diameter	Ft/Pallet		Wt/100'
	10 FT.	20 FT.	10 FT.	20 FT.		10 FT.	20 FT.	
1-1/2"	29.151	29.152	29151 7	29152 4	1.900	2,250	4,500	42
2"	29.201	29.202	29201 9	29202 6	2.375	1,400	2,800	54
3"	29.311	29.302	29301 6	29302 3	3.500	750	1,500	100
4"	29.401	29.402	29401 3	29402 0	4.500	570	1,140	140
6"	29.601	29.602	29601 7	29602 4	6.625	260	520	250
8"	29.801	29.802	29801 1	29802 8	8.625	140	280	389

PVC-DWV COEX Cellular Core meets the requirements of ASTM F 891

NSF-dwv I/O

and the inner and outer wall thickness requirement of the Uniform Plumbing Code (UPC)

CoEx Cellular for non-pressure applications only

PVC DWV SCHEDULE 40 COEX CELLULAR CORE BELLED END/20 FT. LENGTHS

Nominal Size	Item Number	Bar Code 7 17141	Outside Diameter	Min. Wall Thickness	Bell Depth (inch)	Ft/Pallet	Wt/100'
3"	29.322	29322 1	3.500	0.216	4 1/4	1,500	100
4"	29.422	29422 8	4.500	0.237	5	1,140	140
6"	29.622	29622 2	6.625	0.280	6	520	250

PVC-DWV COEX Cellular Core meets the requirements of ASTM F 891

NSF-dwv I/O

and the inner and outer wall thickness requirement of the Uniform Plumbing Code (UPC)

CoEx Cellular for non-pressure applications only