

Silver-Line Plastics

PVC SDR 21 PR 200 PVC 1120 TYPE I GRADE 1

BELLED END 20 FT. LENGTHS

| Nominal Size | Item Number | Bar Code 717141 | Outside Diameter | Min. Wall Thickness | Wt/100' | Ft/Pallet | Max Working Pressure at 73° F |
|---------------------|--------------------|----------------------------|-----------------------------|--------------------------------|----------------|------------------|--|
| 1/2" | 34.052 | 34052 9 | 0.840 | 0.062 | 10 | 9,600 | 315 PSI |
| 3/4" | 34.072 | 34072 7 | 1.050 | 0.060 | 12 | 8,000 | 200 PSI |
| 1" | 34.102 | 34102 1 | 1.315 | 0.063 | 16 | 7,800 | 200 PSI |
| 1-1/4" | 34.122 | 34122 9 | 1.660 | 0.079 | 25 | 5,000 | 200 PSI |
| 1-1/2" | 34.152 | 34152 6 | 1.900 | 0.090 | 33 | 4,500 | 200 PSI |
| 2" | 34.202 | 34202 8 | 2.375 | 0.113 | 53 | 2,800 | 200 PSI |
| 2-1/2" | 34.252 | 34252 3 | 2.875 | 0.137 | 77 | 1,160 | 200 PSI |
| 3" | 34.302 | 34302 5 | 3.500 | 0.167 | 114 | 1,500 | 200 PSI |
| 4" | 34.402 | 34402 2 | 4.500 | 0.214 | 189 | 1,140 | 200 PSI |
| 5" | 34.502 | 34502 9 | 5.563 | 0.265 | 295 | 460 | 200 PSI |
| 6" | 34.602 | 34602 6 | 6.625 | 0.316 | 390 | 520 | 200 PSI |

Note: 2"– 6" are Laying Length

NSF- pw

All SDR 21 conforms to ASTM D 2241; 2" - 6" also meets ASTM F 480; 1/2" is SDR 13.5 and conforms to ASTM D 2241
5" SDR 21 / SCH 40 is dual rated and conforms to D 1785 and D 2241

Material complies with ANSI / NSF Standard 61

**TOO MUCH CEMENT WILL DAMAGE THE PIPE
PVC PIPE NOT RECOMMENDED FOR AIR PRESSURE**